



Colour - Black

DATA / SPECIFICATION SHEET

Natural Rubber (NR)

DESCRIPTION

Natural rubber is a product coagulated from the latex of the rubber tree which used extensively in many applications and products. Natural rubber features low compression set, high tensile strength, resilience, abrasion and tear resistance, good friction characteristics, excellent bonding capabilities to metal substrate, and good vibration dampening characteristics

SERVICE

Resistant to: Mild acids and alkalis, salts and chlorine solutions.

Not suitable for: Petroleum oils, ozone, UV resistance.

PROPERTIES

Density	1.5 g/cc
Tensile Strength	3 MPa
Elongation	200%
Hardness	65 ± 5
Temperature Range	-35 °C to 70 °C

AVAILABILITY

Thickness range	= 1.0mm to 6.0mm (standard) or by order
Standard sheet sizes	= 1.2m X 1.0m 1.2m X 2.0m 1.2m X 5.0m 1.2m X 10.0m

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com