



DATA / SPECIFICATION SHEET

MP 8005I5



**PURE FLEXIBLE GRAPHITE
WITH EXTRA INCONEL WIRES INSERT**

DESCRIPTION

The new Masterpac packing style MP 8005I5 is made from layers of flexible graphite tape plied into compact strands; reinforced with Inconel wires which is subsequently treated with lubricating agents to reduce stem friction and a corrosion inhibitor to prevent pitting. MP 8005I5 is a high-performance valve packing which typically used in power plants, refineries and similar industries where high pressures and high temperatures are prevailing.

AVAILABILITY

Standard Size : 3mm x 3mm to 25mm x 25mm
Standard Weight : 5.5 lbs (2.5 kgs)
11.0 lbs (5.0 kgs)

USE

Min. Temperature : -240°C
Max. Temperature : +650°C (steam)
+455°C (atmosphere)
Max. Pressure : 6000 psi (Valve)
Max. Rotary Speed : n/a
pH Range : 0-14
Construction : Inter-Braided

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com