

LPS[®] **ELECTRA-X** CONTACT CLEANER



FEATURES

- Non-flammable
- Quick penetration
- Fast evaporating
- Non-conductive
- Contains no chlorinated solvents
- No residue
- Safe on most surfaces, may be harmful to some plastics
- Removes oil, grease, and dirt
- Conforms to CARB (California Air Resources Board), OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium)
- Inverta Spray Valve lets you spray in upright or inverted position
- NEW - Environmentally friendly aerosol can contains greater than 50% recycled steel

APPLICATIONS

- Armatures
- Contacts
- Electric Motors
- Electric Relays
- Generators
- Panels
- Printed Circuits
- Switches



PACKAGE

Net Content Part No.
12 wt. oz. / 340 g. / 266 mL aerosol 00816

PROPERTIES

KB Value:
80

Specific Gravity:
1.307

% Non-Volatiles:
<100 ppm

V.O.C. Content:
70.1%, 913 g/L, 7.6 lb./gal.
(aerosol)

Dielectric Strength and
Breakdown Voltage
(ASTM D-877):
9,000 Volts

Flash Point:
None

Propellant:
HFC 134a

Value Performance

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEBSITE: WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Website: www.lpslabs.com

©2011 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2219 • Rev. 7/2011